

FLOCKER 2000™



Automatic Flock Applicator

FEATURES

- Adds flocking capability to most M&R automatic textile presses
- 38 x 43 cm (15" x 17") flock opening
- Accommodates frames 66 x 79 cm (26" x 31") to 69 x 91 cm (27" x 36")



M&R's Flocker 2000 makes it easy to add tightly-registered multi-color flocking capability to most M&R automatic textile presses. The standalone unit has a 38 x 43 cm (15" x 17") flock opening and accommodates frames ranging from (W x L) 66 x 79 cm (26" x 31") to 69 x 91 cm (27" x 36"). Flocker 2000 is activated by the print carriage, and it's compatible with M&R's print start/print finish feature, M&R's patented Optical No-Shirt Detector, and M&R's Skip-Shirt foot pedal.

Locking casters, adjustable height, and a single patch-cord electrical connection make Flocker 2000 easy to move around and set up. Its low-profile flocking box allows for easy loading and cleaning, and it's compatible with the clearances available on most automatic textile presses. Flocker 2000 components can be purchased separately or as a complete turnkey system, with everything necessary to begin flocking. The Flocker 2000 package includes a 66 x 79 cm (26" x 31") 61T stainless steel mesh screen/frame, flocker activation switch, manual foot pedal, ten screen magnets, ten 1.3 mm off-contact spacers, a 61 x 61 cm (24" x 24") magnetic sheet, and a T-Shirt cleaning unit for cleaning excess flock from cured garments. Other components include M&R's Side Frame Holder Assembly with micro-registration and a six-foot ground cable, which supports a 66 x 79 cm

(26" x 31") screen frame below the flocking tray to enable multi-color and/or tightly registered flock application. Unlike some competing flockers, Flocker 2000 does not require printhead removal.

All equipment from The M&R Companies is built with M&R's unsurpassed attention to detail and commitment to quality, durability, innovation, and design excellence, and is backed by M&R's unparalleled 24-hour access to service, support, and premium parts. It's no wonder M&R is the first name in screen printing equipment.

SPECIFICATIONS

	Flocker 2000
Electrical Requirements ¹	115 V, 1 ph, 9 A, 50/60 Hz, 0.7 kW 230 V, 1 ph, 6 A, 50/60 Hz, 0.7 kW
Height (Min/Max)	129 cm/145 cm (51"/57")
Overall Size (L x W)	174 x 63 cm (69" x 25")
Shipping Weight	155 kg (342 lb)

¹ If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly. Other electrical configurations available. Contact The M&R Companies for details



The M&R Companies
M&R • NUARC • AMSCOMATIC

The M&R Companies 1N372 Main Street, Glen Ellyn, Illinois 60137-3576 USA

USA: 800-736-6431 / 630-858-6101 / Fax: 630-858-6134 • Outside USA: +1-847-967-4461 / Fax: +1-847-967-0417

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2007 M&R Printing Equipment, Inc. All rights reserved. 070207